



Technical Data

HALOX® FLASH-X® 150

液体防闪锈剂

产品类型:

通用型水性防闪锈剂

产品概述:

HALOX® FLASH-X® 150用于制造水性防腐蚀涂料,作为一种有效的液体添加剂,用于抑制闪锈和罐内生锈。测试表明,与其他闪锈剂和罐内防锈剂相比,HALOX® FLASH-X® 150在相对较低的添加量下非常有效。HALOX® FLASH-X® 150在各种金属基材上均表现出优异的防闪锈性能,从铁、钢和镀锌铁到镀锌锌和锌铝。

HALOX® FLASH-X® 150可有效抑制衬里和无衬里金属容器中的罐内生锈。

HALOX® FLASH-X® 150 与各种乳液兼容性好,不会导致像其他闪锈添加剂可能出现的薄膜敏感性或包装稳定性问题。HALOX® FLASH-X® 150用于在对金属基材使用表面处理的喷水方法时具有良好的耐腐蚀作用。

HALOX® FLASH-X® 150 易于使用,可以在涂料制造的任何阶段加入。HALOX® FLASH-X® 150 可以轻松有效地添加到任何涂层系统中;但是,与任何添加剂一样,应在使用前检查兼容性。

产品应用*

防闪锈	0.25-1.0%
罐内防腐	0.50-1.5%
金属表面处理	1.50-3.0%

* 建议添加量是以总配方为基准。

Typical Properties

These are typical values and do not represent product specifications:

pH (Neat)	9.6
密度@ 25°C	1.14
外观	清澈透明
颜色	微黄
固含量, %	24

Our Manufacturing Systems are ISO 9001 and ISO 14001 certified

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date hereof, ICL Advanced Additives ("ICL") makes no representations or warranties as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will ICL be responsible for damages of any nature whatsoever resulting from the use or reliance upon Information or the product to which Information refers. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment or formulation in conflict with any patent, and ICL makes no representation or warranty, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

© 2014 ICL Advanced Additives, a division of ICL Performance Products LP. All rights reserved.

Revised 7/29/14

Page 1 of 1